

# Single Contact Bayonet COB BA15S Base



Also fits: Auto1141/1156



## Key Features & Benefits

The new 12V single contact bayonet or BA15S base S8 LED series use COB LED sources and is ideal to replace **Incandescent** and **halogen** bulbs. Available: 3W options. This bulb is highly versatile, which can be retrofitted into **Landscaping** lighting and also **RV, Auto, Boat lighting application** from indicator or cabin lighting to reading lights and offers significant energy savings and environmentally friendly. Light output is 360° which is perfect for even dispersion applications.

## Technical Specifications:

Model Name	JQ-1141-C03K27[2700K] JQ-1141-C03K30[3000K]	JQ-BA-C05K27[2700K] JQ-1141-C05K55[5500K]
Photo		
<b>Halogen Replacement</b>	<b>30 Watt</b>	<b>45 Watt</b>
<b>Operating Voltage:</b>	9 ~ 18V DC/AC	9 ~ 18V DC/ AC
<b>Power consumption:</b>	3 Watt	5 Watt
<b>Dimmable:*</b>	YES	YES
<b>Dimensions:</b>	1.34"x0.71"D	1.34"x0.71"D
<b>CRI:</b>	80+	80+
<b>CCT Option:</b>	2700K (Warm White),3000K	2700K ( Cool White),5500K
<b>Luminous Flux:</b>	300 lm.	400 lm.
<b>Operating Temperature:</b>	-20° C - +50° C	-20° C - +50° C
<b>Storage Temperature:</b>	-30° C - +60° C	-30° C - +60° C
<b>IP Rating</b>	IP67	IP67
<b>Safety Certification:</b>	<b>FCC Compliance</b>	<b>FCC Compliance</b>
<b>Rated Lifespan:</b>	>25,000hrs.	>25,000hrs.

**Notes:** Wattage +/- 10% ; Lumen Values +/- 5Lms. CRI +/- 5% ; Dimmable\* fully tested with LUTRON® DVEL magnetic low voltage dimmer or electrical dimmer with minimum load