




MR16 24V

GU5.3 Base

Key Features & Benefits

The **24V MR16** GU5.3 base LED series is designed for landscaping lighting application. Available:4W, 6W options. As the bulb is rated IP67, it can be used sealed or non-sealed enclosed fixture for damp environment. This series LED light bulbs are highly versatile, which can be used from landscape lighting, deck lighting to tree post lights and offer significant energy savings, and environmentally friendly.

Technical Specifications:

Model Name	JQ-MR16-D04K27V24 JQ-MR16-D04K27V24-60 JQ-MR16-D04K30V24 JQ-MR16-D04K30V24-60	JQ-MR16-D06K27V24 JQ-MR16-D06K27V24-18 JQ-MR16-D06K27V24-60 JQ-MR16-D06K30V24 JQ-MR16-D06K30V24-18 JQ-MR16-D06K30V24-60
Photo		
Halogen Replacement	35 Watt	50 Watt
Operating Voltage:	12 ~ 24V DC/AC	12 ~ 24V DC/AC
Power consumption:	4 Watt	6 Watt
Dimming:	Yes	Yes
Dimensions:	1.61"x1.93"D	1.61"x1.93"D
CRI:	> 81	> 81
CCT Option:	2700K, 3000K	2700K, 3000K
Luminous Flux:	350 lumens	500 lumens
Operating Temperature:	-20° C - +50° C	-20° C - +50° C
Storage Temperature:	-30° C - +60° C	-30° C - +60° C
Lens Bin Option:	36°, 60°	18°,36°, 60°
IP Rating	IP67	IP67
Safety Certification:	ETL, FCC Compliance	ETL, FCC Compliance
Rated Lifespan:	>25,000hrs.	>25,000hrs.

Notes: Wattage +/- 10%; Lumen Values +/- 5Lms. CRI +/- 5%; **Dimmable*** fully tested with LUTRON© DVEL magnetic low voltage dimmer or electrical dimmer with minimum load.

JQ Green America Inc.

San Diego Office: (714)837-7155 Fax: (888)653-8693
Miami Office: (786)397-0999
Houston Office: (772)301-2967

© Copyright 2024 JQ Green America Inc.