



MR8

GU4/Bi-Pin Base

Key Features & Benefits

The MR8 GU4/Bi-Pin base series LED light integrates a set of COB LED light sources into a traditional **MR8 GU4/Bi-Pin base track or cabin** lighting. This product is the ideal solution for indoor or outdoor lighting applications. It meets basic lighting requirements, offers significant energy savings, and is environmentally friendly.

Technical Specifications:

Model Name	JQ-MR8-A03K27M [CCT: 2700K] JQ-MR8-A03K30M [CCT: 3000K]
Photo	
Halogen Replacement	20 Watt
Operating Voltage:	9 ~ 18VAC/DC
Power consumption:	2.5 Watt
Dimming:	Yes
Dimensions:	1"(D) x 1.20"
CRI:	~80
CCT Option:	2700K,3000K
Luminous Flux:	100 lm
Operating Temperature:	-20° C - +50° C
Storage Temperature:	-30° C - +60° C
View Angle	36°
IP Rating	IP54
Safety Certification:	FCC Compliance
Rated Lifespan:	>25,000hrs.

Notes: Wattage +/- 10%; Lumen Values +/- 5Lms. CRI +/- 5%; **Dimmable*** fully tested with LUTRON© magnetic dimmer or electrical dimmer with minimum load.

JQ Green America Inc.

San Diego Office: (714)837-7155 Fax: (888)653-8693
Miami Office: (786)397-0999
Houston Office: (772)301-2967

© Copyright 2024 JQ Green America Inc.