

# PAR36


## Terminal Screw Base



### Key Features & Benefits

The 12V PAR36 Terminal Screw base LED series integrates COB LED sources and is ideal to replace traditional PAR36 **Incandescent** and **halogen** bulbs. Available: 3W, 6W, 12W options. This series LED light bulbs are highly versatile and **rated IP67**, which can be used from landscape damp location such as deck lighting, tree post lights and offer significant energy savings, and is environmentally friendly. Light output is with beam selections of 36° and 60°.

### Technical Specifications:

Model Name	JQ-PAR36-A03K27M JQ-PAR36-A03K27M-60 JQ-PAR36-A03K30M JQ-PAR36-A03K30M-60	JQ-PAR36-A06K27M JQ-PAR36-A06K27M-60 JQ-PAR36-A06K30M JQ-PAR36-A06K30M-60	JQ-PAR36-A12K27M JQ-PAR36-A12K27M-60 JQ-PAR36-A12K30M JQ-PAR36-A12K30M-60
Photo			
Halogen Replacement	20 Watt	35 Watt	50 Watt
Operating Voltage:	9 ~ 15 VAC/DC	9 ~ 15 VAC/DC	9 ~ 15 V DC/AC
Power consumption:	3 Watt	6 Watt	12 Watt
Dimming:	Yes	Yes	Yes
Dimensions:	4.32"(D) x 1.93"	4.32"(D) x 1.93"	4.32"(D) x 1.93"
CRI:	80~ 90	80~ 90	80 ~ 90
CCT Option:	2700k,3000K	2700k,3000K	2700k,3000K
Luminous Flux:	280 lm.	500 lm.	850 lm.
Operating Temperature:	-20° C - +50° C	-20° C - +50° C	-20° C - +50° C
Storage Temperature:	-30° C - +60° C	-30° C - +60° C	-30° C - +60° C
Lens Bin Option:	36°[Std.], 60°	36°[Std.], 60°	36°[Std.], 60°
IP Rating:	<b>IP67</b>	<b>IP67</b>	<b>IP67</b>
Safety Certification:	<b>ETL, FCC Compliance</b>	<b>ETL, FCC Compliance</b>	<b>ETL, FCC Compliance</b>
Rated Lifespan:	>25,000hrs.	>25,000hrs.	>25,000hrs.

**Notes:** Wattage +/- 10%; Lumen Values +/- 5Lms. CRI +/- 5%; **Dimmable\*** fully tested with LUTRON® magnetic dimmer or electrical dimmer with minimum load.

#### JQ Green America Inc.

San Diego Office: (714)837-7155 Fax: (888)653-8693  
 Miami Office: (786)397-0999  
 Houston Office: (772)301-2967

© Copyright 2024 JQ Green America Inc.