

Path Light (PTH)

Key Features & Benefits

Our **New COB** Path Light with voltage options: 12V, 24V and 120V, is retrofitted into existed path lighting fixtures or under the cabinet lighting and is perfect for lighting application along driveway, garden pathway, cabinet, and wall accent lighting etc. It provides much more energy efficiency than any tradition lights, and allows you to create beautiful living life style. Continuous lighting output based on COB technology
5 years no-hassle warranty
LED lighting is also free of environmentally harmful Mercury as well as Halogen chemicals.
Widely used in heavy traffic area such as home, business, school, hotel etc.



Technical Specifications:

Model Name	JQ-PTH2054-C03K27 JQ-PTH2054-C03K30	JQ-PTH2054-C03K30V24	JQ-PTH2105-C03K30V120
Power consumption:	3 Watt	3 Watt	3 Watt
Luminous Flux:	300 lumens	300 lumens	300 lumens
Operating Voltage:	12V-15V	24V-26V	120V
Dimensions:	3" long with 60" wiring	3" long with 60" wiring	3" long with 60" wiring
IP Rating	IP67	IP67	IP67
CRI:	>90	>90	>90
Dimmable*	Yes*	Yes*	Yes*
CCT Options	2700K /3000K	3000K	3000K
Operating Temperature:	-20° C - +50° C	-20° C - +50° C	-20° C - +50° C
Storage Temperature	-30° C - +60° C	-30° C - +60° C	-30° C - +60° C
Rated Lifespan:	>50,000hrs.	>50,000hrs.	>50,000hrs.

Notes: Wattage +/- 10%; Lumen Values +/- 5Lms. CRI +/- 5%, *Dimmable with most magnetic transformers

JQ Green America Inc.

San Diego Office: (714)837-7155 Fax: (888)653-8693
Miami Office: (786)397-0999
Houston Office: (772)301-2967

© Copyright 2024 JQ Green America Inc.